

**6060XXXX COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.XX (LCDOT)**

Effective: January 1, 2007

Revised: June 12, 2014

**Description:** This work shall consist of constructing type B-6.XX concrete curb and gutter.

**Materials:** The materials shall meet the requirements of Article 606.02 of the "Standard Specifications".

**General:** The work shall be performed according to Section 606 of the "Standard Specifications", IDOT Standard Drawing 606001 and the following:

*One inch expansion joints shall be constructed at maximum intervals of 150 feet.*

*The end treatments as shown on the plans shall conform to the applicable special details. Where no end treatment is specified, curb and gutter endings shall be transitioned to a flat section over the final six feet.*

**Method of Measurement:** Combination Concrete Curb and Gutter, Type B-6.24 will be measured for payment in feet. The measurement will be made along the face of curb according to Article 606.14 of the "Standard Specifications". Transitions from one type of curb and gutter to another will be included in the measured quantities for the type having the largest cross sectional area of concrete. *The transition length will be 10 feet unless otherwise shown on the plans.*

**Basis of Payment:** This work will be paid for at the contract unit price per foot for COMBINATION CONCRETE CURB AND GUTTER, of the type specified. *The unit price shall include all equipment, materials and labor required to construct the curb and gutter.*