

## **48203021 HOT-MIX ASPHALT SHOULDERS 6" (LCDOT)**

Effective: January 1, 2007

Revised: May 20, 2014

**Description:** This work shall consist of constructing a hot-mix asphalt (HMA) shoulder on a prepared subgrade behind curb and gutter.

**Materials:** The hot-mix asphalt materials shall meet the requirements of Section 1030 of the "Standard Specifications".

The Hot-Mix Asphalt Base Course will be designed and constructed according to Section 355 of the "Standard Specifications".

The Hot-Mix Asphalt Surface Course will be designed and constructed according to Section 406 of the "Standard Specifications".

**General:** The work shall be performed according to Section 482 of the "Standard Specifications" and the following:

*If the hot-mix asphalt shoulders are part of a larger project involving resurfacing, reconstruction and/or new construction then the surface course shall match the requirements of the surface course used on the rest of the project. If only the hot-mix asphalt shoulders are being constructed then the surface course may consist of Hot-Mix Asphalt Surface Course, Mix "D", N50.*

*The first layer shall consist of 4½" of Hot-Mix Asphalt Base Course and the top layer shall consist of 1½" of Hot-Mix Asphalt Surface Course, of the mixture and gyration specified.*

**Method of Measurement:** Hot-Mix Asphalt Shoulders 6" will be measured for payment according to Article 482.07 of the "Standard Specifications".

**Basis of Payment:** This work will be paid for at the contract unit price per square yard for HOT-MIX ASPHALT SHOULDERS 6". *The unit price shall include all equipment, materials and labor required to construct the HMA shoulder.*