

**LC400150 HOT-MIX ASPHALT SLOPE WALL (LCDOT)** For use on LCDOT let projects only - do not include in IDOT let projects. Delete this note from the Contract Specifications.

Effective: January 1, 2007

Revised: May 20, 2014

**Description:** This work shall consist of constructing a hot-mix asphalt (HMA) slope wall on a prepared earth bed.

**Materials:** The hot-mix asphalt materials shall meet the requirements of Section 1030 of the "Standard Specifications".

The Hot-Mix Asphalt Base Course will be designed and constructed according to Section 355 of the "Standard Specifications".

The Hot-Mix Asphalt Surface Course will be designed and constructed according to Section 406 of the "Standard Specifications".

**General:** The work shall be performed according to Section 511 of the "Standard Specifications", the slope wall details shown on the plans, and the following:

*The hot-mix asphalt material shall be 4½" Hot-Mix Asphalt Base Course and 1½" of Hot-Mix Asphalt Surface Course, Mix "D", N50. Fabric reinforcement will not be required.*

**Method of Measurement:** Hot-Mix Asphalt Slope Wall will be measured for payment in place, and the area computed in square yards. In computing the quantity for payment, the dimensions used will be those established by the Engineer to conform to the elevations of the natural ground line or stream bed. The area for measurement will include the upper, sloped surface of the wall.

**Basis of Payment:** This work will be paid for at the contract unit price per square yard for HOT-MIX ASPHALT SLOPE WALL. *The unit price shall include payment for the preparation of the earth bed; any excavation, backfilling, and/or disposal of surplus material; and furnishing and placing all materials. The unit price shall also include all equipment, materials and labor required to construct the slope wall.*