

Application Rate Guidelines

How long an application will last depends on five factors: pavement temperature, application rate, precipitation, beginning concentration, and chemical type. These factors explain why one application rate will not fit all storm events.

- If your equipment is unable to deliver material at lower rates, consider exchanging the 9-inch-diameter auger for either a 6-inch or 9-inch special auger to deliver about two-thirds less material/revolution.

Anti-icing Application Rate Guidelines

These guidelines are a starting point. Reduce or increase rates incrementally based on your experience.

Condition	Gallons/Lane Mile			Other Products
	CaCl ₂	MgCl ₂	Salt Brine	
1. Regularly scheduled applications	15 – 25	15 – 25	20 – 40	Follow manufacturers' recommendations.
2. Prior to frost or black ice event	15 – 25	15 – 25	20 – 40	
3. Prior to light or moderate snow	15 – 25	15 – 25	20 – 50	

Pounds of Ice Melted Per Pound of Salt

Pavement Temp. °F	One Pound of Salt (NaCl) melts	Melt Times
30	46.3 lbs of ice	5 min.
25	14.4 lbs of ice	10 min.
20	8.6 lbs of ice	20 min.
15	6.3 lbs of ice	1 hour
10	4.9 lbs of ice	Dry salt is ineffective and will blow away before it melts anything.
5	4.1 lbs of ice	
0	3.7 lbs of ice	
-6	3.2 lbs of ice	

At temps below 15 degrees, it may be more cost-effective to use a chemical other than NaCl.

See research at www.dot.state.mn.us/maintenance/training

Deicing Application Rate Guidelines 24' of pavement (typical two-lane road)

These rates are not fixed values, but rather the low end of a range to be selected and adjusted by an agency according to its local conditions and experience.

Pavement Temp. (°F) and Trend (↑↓)	Weather Condition	Maintenance Actions	Lbs/ two-lane mile			
			Salt Prewetted/ Pretreated With Salt Brine	Salt Prewetted/ Pretreated With Other Blends	Dry Salt*	Winter Sand (abrasives)
>30° ↑	Snow	Plow, treat intersections only	80 (40/lane mile)	70	100*	Not recommended
	Frz. rain	Apply chemical	80 – 160	70 – 140	100 – 200*	Not recommended
30° ↓	Snow	Plow & apply chemical	80 – 160	70 – 140	100 – 200*	Not recommended
	Frz. rain	Apply chemical	150 – 200	130 – 180	180 – 240*	Not recommended
25 - 30° ↑	Snow	Plow & apply chemical	120 – 160	100 – 140	150 – 200*	Not recommended
	Frz. rain	Apply chemical	150 – 200	130 – 180	180 – 240*	Not recommended
25 - 30° ↓	Snow	Plow & apply chemical	120 – 160	100 – 140	150 – 200*	Not recommended
	Frz. rain	Apply chemical	160 – 240	140 – 210	200 – 300*	400
20 - 25° ↑	Snow or frz. rain	Plow & apply chemical	160 – 240	140 – 210	200 – 300*	400
20 - 25° ↓	Snow	Plow & apply chemical	200 – 280	175 – 250	250 – 350*	Not recommended
	Frz. rain	Apply chemical	240 – 320	210 – 280	300 – 400*	400
15 - 20° ↑	Snow	Plow & apply chemical	200 – 280	175 – 250	250 – 350*	Not recommended
	Frz. rain	Apply chemical	240 – 320	210 – 280	300 – 400*	400
15 - 20° ↓	Snow or Frz. rain	Plow & apply chemical	240 – 320	210 – 280	300 – 400*	500 for frz. rain
0 to 15° ↑↓	Snow	Plow, treat with blends, sand hazardous areas	Not recommended	300 – 400	Not recommended	500 – 750 spot treat as needed
< 0°	Snow	Plow, treat with blends, sand hazardous areas	Not recommended	400 – 600**	Not recommended	500 – 750 spot treat as needed

*Dry salt is not recommended. It is likely to blow off the road before it melts ice.

**A blend of 6 – 8 gal/ton MgCl₂ or CaCl₂ added to NaCl can melt ice as low as -10°.