

**4420XXXX CLASS B PATCHES, TYPE X, X INCH (LCDOT)** For use on LCDOT projects. Fill in the thickness of the concrete "X" in the first bullet. Delete this note from the Contract Specifications.

Effective: March 29, 2019

Revised:

**Description:** This work shall consist of removing the existing pavement, excavating the subgrade if necessary, and placing new pavement - class B patch(s) of the type and thickness specified, at locations designated by the Engineer.

**Materials:** The materials shall meet the requirements of Article 442.02 of the "Standard Specifications".

**Equipment:** The equipment shall meet the requirements of Article 442.03 of the "Standard Specifications".

**General:** The work shall be performed according to Section 442 of the "Standard Specifications" and the following:

- *The pavement patching shall be limited to X" of Portland Cement Concrete.*
- *The debris and slurry produced by the sawcutting and removal operation shall be contained at the removal site and prevented from entering adjacent drainage systems. The debris and slurry shall be disposed of according to Article 202.03 of the "Standard Specifications".*
- *In the event the debris and slurry are not contained an erosion and/or sediment control deficiency will exist and a daily monetary deduction will be imposed according to Article 105.03 (a) of the "Standard Specifications".*

**Method of Measurement:** Class B Patches, of the type and depth specified will be measured for payment in place, and the area computed in square yards.

**Basis of Payment:** CLASS B PATCHES, of the type and depth specified will be paid for at the contract unit price per square yard. *The unit prices shall include all equipment, materials and labor required to remove and dispose of the existing pavement; contain, remove and dispose of the debris and slurry; and to install the patch(s).*